



#### **General information**

**HybridRED CR** is one-component coating paste with very high inorganic content designed to revive worn or scratched surfaces. It can be used as final layer as it cross-links within hours under ambient moisture to form a stable layer that provides protection against weathering.

It can be applied on various materials but is prominently designed for substrates originally coated with HybridRED fire protection coating.

# **Key properties**

- weather and UV resistant
- available in clear and RAL colors
- non-toxic, does not contain halogens or antimony trioxide
- no effect on the performance of the original substrate

### **General properties**

- 1-component paste
- solvent based
- fast tack-free time
- no need for post-curing
- wide application window


# **Applications**

- restoration of the color of scratched or worn surfaces
- decorative and industrial applications
- resurfacing damaged FR gelcoat
- indoor and outdoor

### Usage

**HybridRED CR** is ready-to-use and can be applied by brush or cloth but needs finishing with a dry cloth. As it is not a film forming material, excess material needs to be removed. It is applied as a wax.







2019-09-03- · version 1.0

# Safety and Handling

The content of an opened package is influenced by air moisture. Keep tightly capped when not in use. Handle in a well-ventilated area. Store indoors at room temperature in the original containers kept tightly closed. Protect form direct sun light. Detailed safety information is contained in a material data safety sheet.